

Our range of service at a glance

Material: Hot-rolled strip, black or pickled
Strengths up to 1000 N/mm²
Cold-rolled strip, thin sheet
Galvanised and surface-finished material
Stainless steel, ferritic or austenitic qualities*
Aluminium, in rolled version*
Brass in rolled or milled version*
Titanium in annealed version*

Machine fleet: 5 circular shears
1 roller

Input widths: 50–1780 mm

Thickness range: 0.25–16.00 mm


Coil weight: Input and output max. 32 tonnes.

Ring outer dia.: Decoiler and recoiler max. 2000 mm

Ring inner dia.: Decoiler 400–800 mm
Recoiler 508 and 610 mm

Strip widths: From 19 mm

* only for contract trade



Number of strips: Max. 37 strips (depending on material and thickness)

Processing: Splitting, trimming, cross-cutting, rereeling, changing inner and outer diameters, rolling

Rollers: Thickness 0.50–6.00 mm
Width 25–300 mm

Material testing: Own material testing centre

Storage capacity: Raw strip storage > 60,000 tonnes /
finished goods storage > 10,000 tonnes

Capacity: > 300,000 tonnes p.a.

If you have any questions about our portfolio or would like advice, please contact our steel experts.

Your OKS Team

* only for contract trade